



Solar Flat Plate Collectors

- 25,000, 50,000 & 75,000 Btu/day (SRCC Cat. C)
- Universal mounts for flush roof or ground mount.
- Durable, 1/8", low iron tempered glass.
- Selective crystal coating absorber coating.
- Attractive bronze extruded aluminum frame.
- SRCC certified and listed.
- 10-year warranty.



SolarFlex™ Insulated Flexible Stainless Steel Piping

- 3/4" x 50 feet continuous coil.
- High temperature EPDM insulation UV resistant.
- Heavy durable UV resistant film outside jacket.
- Sensor wire between flow and return pipes.
- 6-year warranty.



SolarCon™ Storage Tank

- 50, 80 & 119 gallon tanks with lower heat exchanger coil and electrical element for backup heating.
- 4,500 watt, UL listed backup element with aquastat.
- 80 & 119 gallon tanks with lower heat exchanger coil and upper heat exchanger coil for boiler backup heating.
- Durable porcelain enamel lining, with protective cobalt.
- Heavy gauge powdered coated steel outside jacket.
- Thick 2" non CFC foam insulation.
- Dual heavy-duty anode rods protection.
- 6-year warranty.



iSolar™ Differential Temperature Controller and Solar Station

- LCD user friendly graphic display.
- Variable pump speed control.
- Collector overheat protection.
- Storage tank cooling.
- kWh energy measurement.
- Adjustable delta T function.
- Shut off valves with built-in flow checks.
- Fill and purge plus safety valves.
- Flow meter and flow adjustment.
- Temperature and pressure gages.
- Three speed pump, UL listed.
- 4-year warranty with authorized installer.